

## **Calpeda**

Calpeda Pressure tank is an essential part of a pressurized water system that provides water pressure at a set level. The tank stores supplemental water between diaphragm and liner, and the pressurized air chamber is able to create a supply circle. This process reduces the number of times the motor need to start in order for the system pressure to remain at the set level.

The tension of diaphragm maintains water pressure within the system, ensuring proper operation of the dishwasher and washing machine, and robust flow for showering and bathing. Calpeda pressure tank is an energy saving device and no maintenance is needed. A properly sized pump and pump tank will work as a team to meet your needs and will deliver many years of dependable service.

**(E** 2459

PSB SS375















	CALPEDA VERTICAL PRESSURE TANK																
Model Number		Tank ume	Connector	Diameter		Height Base Including		BOX Length		BOX Width		BOX Height		N.W.		GW	
Number	Liter	Gal	Size	cm	Inch	cm	Inch	cm	Inch	cm	Inch	cm	Inch	Kg	Lbs	Kg	Lbs
PTV-3A	3	0.5	1" BSP	13.0	5.1	21.5	8.5	31.0	12.2	30.0	11.8	24.0	9.5	4.1	9.0	4.7	10.4
PTV-18A	18	4.5	1" BSP	28.0	11.0	39.0	15.4	28.5	11.2	28.5	11.2	39.5	15.6	3.3	7.3	3.7	8.2
PTV-24A	24	6.0	1" BSP	29.5	11.6	41.5	16.3	31.0	12.2	31.0	12.2	44.5	17.5	3.9	8.6	4.8	10.6
PTV-40A	40	10.0	1" BSP	29.5	11.6	55.0	21.7	31.0	12.2	31.0	12.2	57.0	22.5	5.9	13.0	6.8	15.0

## **STAND MODELS WITH BASE**

Model	Total Tank Volume		Connector	Diameter		Height Base Including		BOX Length		BOX Width		BOX Height		N.W.		GW	
Number	VOI	ume	c:			Base Ir	iciuaing	Len	igtn	VVI	atn	не	ignt				
Number	Liter	Gal	Size	cm	Inch	cm	Inch	cm	Inch	cm	Inch	cm	Inch	Kg	Lbs	Kg	Lbs
PTV-60A	60	14.0	1"BSP	38.1	15.0	60.0	23.6	41.0	16.2	41.0	16.2	62.0	24.4	9.7	21.4	11.0	24.3
PTV-100A	100	28.0	1" BSP	43.0	16.9	76.5	30.0	44.0	17.3	44.0	17.3	78.8	31.0	13.3	29.3	15.2	33.0
PTV-200A	200	53.0	1-1/4" BSP	55.9	22.0	100.5	39.6	56.0	22.1	56.0	22.1	102.5	10.4	29.5	65.1	32.8	72.4
PTV-305A	305	81.0	1-1/4" BSP	55.9	22.0	145.0	57.1	56.0	22.1	56.0	22.1	147.0	57.9	41.1	90.7	47.1	103.9
PTV-450A	450	120.0	1-1/4" BSP	65.0	25.6	140.0	55.2	69.0	27.1	69.0	27.1	144.0	56.7	56.5	124.6	61.5	135.6
PTV-500A	500	132.0	1-1/4" BSP	65.0	25.6	156.6	61.7	69.0	27.1	69.0	27.1	178.0	70.0	62.0	137.0	67.0	148.0

## **CALPEDA HORIZONTAL TANK WITH BASE**

Model Number		Tank ume	Diam	neter		ght cluding		OX ngth	B( Wi	OX dth		OX ight	N.	W.	G	w
Number	Liter	Gal	cm	Inch	cm	Inch	cm	Inch	cm	Inch	cm	Inch	Kg	Lbs	Kg	Lbs
APT-24H	24	6.0	29.5	11.6	32.0	12.6	41.5	16.3	43.0	17.0	34.0	13.4	4.8	10.6	5.4	11.9
APT-40H	40	10.0	29.5	11.6	32.0	12.6	55.0	21.7	60.0	23.6	34.5	13.4	6.5	14.4	7.4	16.4
APT-60H	,60	14.0	38.1	15.0	42.5	17.0	53.0	22.0	54.0	21.3	45.0	45.0	9.8	21.7	11.1	24.5



**PSB** 











SHELL	SYSTEM CONNECTION	COATING	DIAPHRAGM
Cold Rolled Carbon Steel	304 Stainless Steel Connector	Triple Grade Blue Paint	Butyl Rubber Non-Changeable Membrane Type
LINER MATERIAL	FACTORY PRE-CHARGE	MAX WORKING TEMPERATURE	MAX WORKING PRESSURE
FDA Grade Polypropylene	30 PSI / 2 Bar	93°C / 200°F	150 PSI / 10 Bar



**CONTACT US** 



www.calpeda.co.th